



PRODUCT IMAGE

**CARTRIDGE TYPE:** CE  
**MEDIA TYPE:** BLEACHED COTTON

**DESCRIPTION:** Bleached to meet FDA requirements for the potable liquids, vegetable oils, beverages, organic solvents, water, dilute acids, petroleum oils and other services. \*Available for industrial and/or FDA applications.

**CENTER CORE:** Tin, S/S304, S/S316, Polypropylene

**END TREATMENT:** Metal cap w/top spring, Poly Flat Cap, Poly Fin, Poly Spring

**INSIDE DIAMETER:** 1"

**OUTSIDE DIAMETER:** 1.75", 2", 2.125", 2.375", 2.4375", 2.50", 2.625", 2.75", 3", 4", 4.25", 4.5", 6"

**MICRON RATINGS:** 5, 1, 3, 5, 10, 15, 20, 25, 30, 50, 75, 100, 150, 200

**LENGTH:** 5" - 72"

**RECOMMENDED CHANGE OUT:** 35 PSID

**FLOW RATE:** 0 - 6 GPM Per 2.5"x10" Length

**MAXIMUM MEDIA TEMPERATURE:** 300 F



**MEDIA**

CE	Bleached Cotton
CF	FDA Bleached Cotton
CE	White (bleached) Cotton
PF	Twisted Fibrillated Poly
FP	FDA Polypropylene
EP	Polypropylene
NY	Nylon
RA	Rayon
PE	Polyester
FG	Fiberglass
* CALL FOR OTHERS	

**MICRON RATINGS**

.5	1	3	5
15	20	25	30
50	75	100	
125	150	200	

**ELEMENT DIAMETER**

R-2 1/4 = 2.125, F-2 3/8 = 2.375, C-2 7/16 = 2.4375  
 R-2 1/2 = 2.5, S-2 3/4 = 2.75, L-4 1/4 = 4.25, W-3"  
 X-4 1/2 = 4.5, G-2", Q-4", N-2 5/8 = 2.625  
 B-1 3/4 = 1.75, Z-5 1/2 = 5.5, Y-6"

**INCHES LENGTH**

5, 9 3/4, 10, 12, 12 1/2, 19 1/2, 20, 27  
 29 1/2, 30, 36, 39, 40, 50, 60, 68, 70, 72  
 \*SPECIAL LENGTHS AVAILABLE UPON REQUEST

**CORE EXTENSION**

PE	Poly Extender
S/S	Extender

**END TREATMENT**

MCS	Metal Cap w/topspring
PFC	Poly Flat Cap
PFN	Poly Fin (Spear)
PSC	Poly Spring
222	End Cap
226	End Cap

**CORE COVER**

CC	Core Cover
V	Specified Cover
CB	Carbon Cover

**O-RING MATERIAL**

S	Silicon
B	Buna
V	Viton

**CORE MATERIAL**

P	Polypropylene
T	Tin Plated Steel
S	304 Stainless Steel
A	316 Stainless Steel

\*SPECIAL LENGTHS AVAILABLE UPON REQUEST

NOMENCLATURE

Information and data presented here is believed to be reliable but is not warrant of product performance. Verification testing is recommended to determine suitability for any particular use. Actual cartridge performance will vary with liquid conditions. Product characterizations are based on the average performance of duplicate cartridge's samples selected at random.