



PRODUCT IMAGE

CARTRIDGE TYPE: MEDIA TYPE:

CF
BLEACHED COTTON

DESCRIPTION:

Bleached to meet FDA requirements for the potable liquids, vegetable oils, beverages, organic solvents, water, dilute acids, petroleum oils and other services.
*Available for industrial and/or FDA applications.

CENTER CORE:

S/S304, S/S316, Polypropylene

END TREATMENT:

Poly Flat Cap, Poly Fin, Poly Spring

INSIDE DIAMETER:

1"

OUTSIDE DIAMETER:

1.75", 2", 2.125", 2.375", 2.4375", 2.50", 2.625", 2.75", 3", 4", 4.25", 4.5", 6"

MICRON RATINGS:

5, 1, 3, 5, 10, 15, 20, 25, 30, 50, 75, 100, 150, 200

LENGTH:

5" - 72"

RECOMMENDED CHANGE OUT: FLOW

35 PSID

RATE:

0 - 6 GPM Per 2.5"x10" Length

MAXIMUM MEDIA TEMPERATURE:

300 F



MEDIA

- CE Bleached Cotton
- CF FDA Bleached Cotton
- CE White (bleached) Cotton
- FIB Twisted Fibrillated Poly
- FP FDA Polypropylene
- EP Polypropylene
- NY Nylon
- RA Rayon
- PE Polyester
- FG Fiberglass
- * CALL FOR OTHERS

CORE EXTENSION

- PE Poly Extender
- S/S Extender

NOMENCLATURE

END TREATMENT

- PFC Poly Flat Cap
- PFN Poly Fin (Spear)
- PSC Poly Spring
- 222 End Cap
- 226 End Cap

MICRON RATINGS

.5	1	3	5
15	20	25	30
50	75	100	
125	150	200	

CORE COVER

- CC Core Cover
- V Specified Cover
- CB Carbon Cover

ELEMENT DIAMETER

E-2 ¼ = 2.125, F-2 3/8 = 2.375, C-2 7/16 = 2.4375 R- 2 ½ = 2.5, S- 2 ¾ = 2.75, L- 4 ¼ = 4.25, W-3" X-4 ½ = 4.5, G-2", Q-4", N- 2 5/8 = 2.625 B- 1 ¼ = 1.75, Z-5 ½ = 5.5, Y- 6"

INCHES LENGTH

5, 9 3/4, 10, 12, 12 1/2, 19 1/2, 20, 27, 29 1/2, 30, 36, 39, 40, 50, 60, 68, 70, 72

*SPECIAL LENGTHS AVAILABLE UPON REQUEST

O-RING MATERIAL

- S Silicon

CORE MATERIAL

- P Polypropylene
- S 304 Stainless Steel
- A 316 Stainless Steel

*SPECIAL LENGTHS AVAILABLE UPON REQUEST

Information and data presented here is believed to be reliable but is not warrant of product performance. Verification testing is recommended to determine suitability for any particular use. Actual cartridge performance will vary with liquid conditions. Product characterizations are based on the average performance of duplicate cartridge's samples selected at random.