

PRODUCT IMAGE



CARTRIDGE TYPE: MEDIA TYPE:

FIB
FIBRILLATED
POLYPROPYLENE

DESCRIPTION:

Non-migrating slit film polypropylene is used with ultra-pure liquids, electronics, and plating where non-leaching is critical. Chemical resistance is equal to standard polypropylene.

CENTER CORE:

Tin Core, S/S304, S/S316, Polypropylene

END TREATMENT:

Metal cap w/top spring, Poly Flat Cap, Poly Fin, Poly Spring, 222 End Cap, 226 End Cap 1"

INSIDE DIAMETER:

1.75", 2", 2.125", 2.375", 2.4375", 2.50", 2.625", 2.75", 3", 4", 4.25", 4.5", 6"

OUTSIDE DIAMETER:

.5, 1, 3, 5, 10, 15, 20, 25, 30, 50, 75, 100, 150, 200

MICRON RATINGS:

5" - 72"

LENGTH:

35 PSID

RECOMMENDED CHANGE OUT:

0 - 6 GPM Per 2.5"x10" Length

FLOW RATE:

150 F

MAXIMUM MEDIA TEMPERATURE:

MEDIA

CU	NATURAL COTTON
CE	BLEACHED COTTON
CF	FDA BLEACHED COTTON
FIB	FIBRILLATED POLYPRO.
FP	FDA POLYPROPYLENE
EP	POLYPROPYLENE
NY	NYLON
RA	RAYON
PE	POLYESTER
FG	FIBERGLASS

MICRON RATINGS

.5	1	3	5
15	20	25	30
50	75	100	
125	150	200	

ELEMENT DIAMETER

E-2 1/4 = 2.125, F-2 3/8 = 2.375, C-2 7/16 = 2.4375 R-2 1/2 = 2.5, S-2 3/4 = 2.75, L-4 1/4 = 4.25, W-3" X-4 1/2 = 4.5, G-2", Q-4", N-2 5/8 = 2.625
B-1 3/4 = 1.75, Z-5 1/2 = 5.5, Y-6"

INCHES LENGTH

5, 9 3/4, 10, 12, 12 1/2, 19 1/2, 20, 27
29 1/2, 30, 36, 39, 40, 50, 60, 68, 70, 72

*SPECIAL LENGTHS AVAILABLE UPON REQUEST

FIB 20 R 40 P --- --- ---

NOMENCLATURE

CORE EXTENSION

PE Poly Extender
S/S Extender

END TREATMENT

MCS Metal Cap w/topspring
PFC Poly Flat Cap
PFN Poly Fin (Spear) Poly
PSC Spring
222 End Cap
226 End Cap

CORE COVER

CC Core Cover
V Specified Cover
CB Carbon Cover

O-RING MATERIAL

S Silicon
B Buna
V Viton

CORE MATERIAL

P Polypropylene Tin
T Plated Steel 304
S Stainless Steel 316
A Stainless Steel

*SPECIAL LENGTHS AVAILABLE UPON REQUEST

Information and data presented here is believed to be reliable but is not warrant of product performance. Verification testing is recommended to determine suitability for any particular use. Actual cartridge performance will vary with liquid conditions. Product characterizations are based on the average performance of duplicate cartridge's samples selected at random.