



PRODUCT IMAGE

**CARTRIDGE TYPE:** EP  
**MEDIA TYPE:** INDUSTRIAL POLYPROPYLENE  
**USE:** Available for home and Commercial Use.

**DESCRIPTION:** Filtration of water, potable liquids, animal and vegetable oils, organic acids, alkalis, and many other chemicals.

- Available for industrial and/or FDA applications.
- Available for home and Commercial use.

**CENTER CORE:** Tin, S/S304, S/S316, Polypropylene

**END TREATMENT:** Metal cap w/top spring, Poly Flat Cap, Poly Fin, Poly Spring

**INSIDE DIAMETER:** 1"

**OUTSIDE DIAMETER:** 1.75", 2", 2.125", 2.375", 2.4375", 2.50", 2.625", 2.75", 3", 4", 4.25", 4.5", 6"

**MICRON RATINGS:** .5, 1, 3, 5, 10, 15, 20, 25, 30, 50, 75, 100, 150, 200

**LENGTH:** 5" - 72"

**RECOMMENDED CHANGE OUT:** 35 PSID

**FLOW RATE:** 0 - 6 GPM Per 2.5"x10" Length

**MAXIMUM MEDIA TEMPERATURE:** 150 F

### MEDIA

- CU Natural Cotton
- CF FDA Bleached Cotton
- CE White (bleached) Cotton
- PF Twisted Fibrillated Poly
- FP FDA Polypropylene
- EP Polypropylene**
- NY Nylon
- RA Rayon
- PE Polyester
- FG Fiberglass
- \* CALL FOR OTHERS

### MICRON RATINGS

|     |     |     |    |
|-----|-----|-----|----|
| .5  | 1   | 3   | 5  |
| 15  | 20  | 25  | 30 |
| 50  | 75  | 100 |    |
| 125 | 150 | 200 |    |

### ELEMENT DIAMETER

- E-2 1/4 = 2.125, F-2 3/8 = 2.375, C-2 7/16 = 2.4375
- R-2 1/2 = 2.5, S-2 3/4 = 2.75, L-4 1/4 = 4.25, W-3"
- X-4 1/2 = 4.5, G-2", Q-4", N- 2 5/8 = 2.625
- B-1 3/4 = 1.75, Z-5 1/2 = 5.5, Y- 6"

# NOMENCLATURE



### CORE EXTENSION

- PE Poly Extender
- S/S Extender

### END TREATMENT

- MCS Metal Cap w/topspring
- PFC Poly Flat Cap
- PFN Poly Fin (Spear)
- PSC Poly Spring
- 222 End Cap
- 226 End Cap

### CORE COVER

- CC Core Cover
- V Specified Cover
- CB Carbon Cover

### O-RING MATERIAL

- S Silicon
- B Buna
- V Viton

### CORE MATERIAL

- P Polypropylene
- T Tin Plated Steel
- S 304 Stainless Steel
- A 316 Stainless Steel

\*SPECIAL LENGTHS AVAILABLE UPON REQUEST

Information and data presented here is believed to be reliable but is not warrant of product performance. Verification testing is recommended to determine suitability for any particular use. Actual cartridge performance will vary with liquid conditions. Product characterizations are based on the average performance of duplicate cartridge's samples selected at random.